

PRESSURE

PRESIÓN

- 8 435277 946102
- 8 435277 946119
- 8 435277 946126
- 8 435277 946133
- 8 435277 946140
- 8 435277 946157
- 8 435277 946164
- 8 435277 946171
- 8 435277 946188
- 8 435277 946201
- 8 435277 946218
- 8 435277 946225
- 8 435277 946232
- 8 435277 946249
- 8 435277 946256
- 8 435277 946263
- 8 435277 946270
- 8 435277 946287
- 8 435277 946317
- 8 435277 946324
- 8 435277 946331
- 8 435277 946348
- 8 435277 946355
- 8 435277 946362



CODO FITTING IGUAL
FITTING ELBOW P.E.
COUDE PRESSION P.E.
FITTING JOELHO

ФИТИНГ УГОЛЬНИК РАВНОЗНАЧНЫЙ

Ref.	Ø(mm)	u/b	u/c	Dimensiones A-B-C
4610	16	1	100	88X88X41
4611	20	1	100	88X88X41
4612	25	1	100	104X104X48
4613	32	1	100	125X125X57
4614	40	-	40	142X142X67
4615	50	-	20	172X172X83
4616	63	-	12	205X205X104
4617	75	-	6	
4618	90	-	6	



CODO FITTING MACHO
MALE THREADED FITTING ELBOW P.E.
COUDE PRESSION FILETÉ P.E.
FITTING JOELHO RM

ФИТИНГ УГОЛЬНИК С ВНЕШНЕЙ РЕЗЬБОЙ

Ref.	Ø(mm-")	u/b	u/c	Dimensiones A-B-C
4620	16-1/2	1	100	82X67X41
4621	20-1/2	1	100	82X67X41
4622	25-3/4	1	100	97X76X48
4623	32-1	1	100	116X87X57
4624	40-1 1/4	-	30	135X104X68
4625	50-1 1/2	-	30	160X125X93
4626	63-2	-	20	192X157X103
4627	75-2 1/2	-	6	
4628	90-3	-	6	



CODO FITTING HEMBRA P.E.
FEMALE THREADED FITTING ELBOW P.E.
COUDE PRESSION TARAUDÉ P.E.
JOELHO RF

ФИТИНГ УГОЛЬНИК С ВНУТРЕННЕЙ РЕЗЬБОЙ

Ref.	Ø(mm-")	u/b	u/c	Dimensiones A-B-C
4631	20-1/2	1	100	84X54X41
4632	25-3/4	1	100	97X61X48
4633	32-1	1	100	117X80X57
4634	40-1 1/4	-	30	137X98X68
4635	50-1 1/2	-	30	161X101X82
4636	63-2	-	20	195X124X103



Llave apretar fitting ver apartado de herramientas.

CARACTERISTICAS FITTING

- Accesorios para tubería de presión, fabricados en P.D.F.V. ingles (Polipropileno con Fibra de Vidrio) en las proporciones adecuadas en cuerpos y tuercas.
- Prisioneros de Poliamida.
- Arandela en A.B.S.
- Juntas tóricas.

Este producto, por su especial diseño tanto exterior como interior, está preparado p tuberías de 4-6-10-16 ATM P.E.B.D. (Polietileno Baja Densidad). Además tener en cuenta evidentemente los diámetros de tuberías que están calibrados en su medida toda uniforme.

Las distintas referencias de roscas machos y roscas hembras están preparadas par ser roscadas en accesorios que presten las medidas adecuadas en sus roscas en producto P.P.

Se recomienda que la manguera tenga un corte limpio y homogéneo en su círculo, i presentar la manguera chafada, por lo que ganaremos rapidez en su montaje y obtendremos un resultado positivo en todo su conjunto de ensamblaje.

Torque wrench for tightening fitting see our tools section

FITTING CHARACTERISTICS

- Accessories for pressure pipes, made of P.D.F.V. (polyethylene with fibreglass) with bodies and threaded connectors made in adequate proportions.
- Polyamide fasteners.
- A.B.S. washers.
- O-Rings

This product is ready for 4-6-10-16 ATM P.E.B.D. (low density polyethylene) thanks both its outer and interior design. Please, bear in mind that the pipe diameters are e and proportionally well calibrated.

Different referencies of male and female threaded connectors are ready to be screw on/in accessories that present suitable measures on their threaded connectors, and P.P. product.

It is recommended to have the hose with a clean uniform cut on the diameter. Do no present a squashed hose, so we can speed up the installation process and obtain positive results in the assembly.